



EURASIA PETROL
Trading of Petroleum Products

PRODUCT DATA SHEET

Product Category	Product Name	Grade
Oil & Gas	Base Oil	Base Oil

Characteristic	SN 150-A	SN 500	SN 600	SN 650	Bright Stock	Test method ASTM
Kinematic viscosity @ 100DC,cSt	4.9 Min 6.5 Max	11 Min Max	12 Min Max	13 Min 14.5 Max	28 Min 32 Max	D-445
Viscosity index (VI)	90 Min	90 Min	90 Min	85 Min	90 Min	D-2270
Flash point, DC	205 Min	235 Min	250 Min	260 Min	300 Min	D-92
Pour point, DC	-3 Max	-6 Max	-6 Max	-6 Max	-6 Max	D-97
Specific gravity@15.6DC/ 15.6DC	0.870	0.885	0.890	0.895	0.900	D-1298
Sulphur content, (wt%)	0.5	0.4	0.6	0.7	1	D-2622
Color	2.5 Max	2 Max	2.5 Max	3 Max	4 Max	D-1500
NOAK (wt%)	10	6	6	5	2	D-5800
CARBON RESIDUE CONTENT, (wt%)	0.05	0.1	0.2	0.2	0.3	D-189

Application	As fuel for power plants and using in vessel engine
Packaging	Bulk



+90 24 22 44 55 85



www.Eurasiapetrol.com
Info@Eurasiapetrol.com



Adnan menderes blv, Tahıl pazarı neighborhood,
Emka building, no:22, Muratpaşa, Antalya, Turkey.