



EURASIA PETROL
Trading of Petroleum Products

PRODUCT DATA SHEET

Product Category	Product Name	Grade
Oil & Gas	Kerosene	Kerosene

Analysis	Unit	Limit	Test Method
Distillation			ASTM D86
Recovered @ 185 DC (max)	%vol	50	ASTM D86
Recovered @ 200 DC (min)	%vol	20	ASTM D86
Recovered @ 210 DC (max)	%vol	90	ASTM D86
Recovered @ 235 DC (max)	%vol	95	ASTM D86
F.B.P (max)	DC	275	ASTM D86
Residue (max)	%vol	2.0	ASTM D86
Loss (max)	%vol	1.5	ASTM D86
Corrosion 3 hr @ 100 DC		1a	ASTM D130
Density @ 15 DC (max)	Kg/m3	820	ASTM D1298
Colour (min)		25	ASTM D156
Odor		merchantable	
Flash Point (min)	DC		ASTM D93
Smoke point (min)	mm	25	IP 57
Sulphur Total (max)	Wt%	0.15	ASTM D1266
Mercaptan sulphur (max)	Wt%	0.0010	ASTM D3227

Application	As Fuel
Packaging	Bulk



+90 24 22 44 55 85



www.Eurasiapetrol.com
Info@Eurasiapetrol.com



Adnan menderes blv, Tahilpazarı neighborhood,
Emka building, no:22, Muratpaşa, Antalya, Turkey.