



EURASIA PETROL  
Trading of Petroleum Products

## PRODUCT DATA SHEET

Product Category	Product Name	Grade
Polymers	POLYETHYLENE – LLDPE	LL0209 KJ

Property	Test Method ASTM	Unit	Value
MFI@190° C, 2.16 kg	D1238	gr/10min	0.9
Density	D2839	gr/ml	0.920
Vicat Softening Point	D1525	°C	100
Tensile Strength @Yield, MD/TD	D638	Mpa	10.5/11
Elongation @ Break, MD/TD	D638	%	620/840
Tensile Strength @ Break, MD/TD	D688	Mpa	41/32
Tear Strength, MD/TD	D1922	gr/25mic	145/370
Impact Strength, Dart	D1709	gr	150
Haze	D1003	%	10
Gloss (45°)	D2457	Rating	56

<b>Application</b>	It is suitable for application in Shrink hoods, Industrial sacks, Heavy duty, carrier bags and liners
<b>Packaging</b>	25 Kg plastic bag



+90 24 22 44 55 85



www.Eurasiapetrol.com  
Info@Eurasiapetrol.com



Adnan menderes blv, Tahilpazarı neighborhood,  
Emka building, no:22, Muratpaşa, Antalya, Turkey.